



HKC

SecureHub

Wireless Alarm Panel

Smarter Security

The HKC SecureHub is a Grade 2 alarm panel with onboard SecureWave 2-way wireless technology and supports a range of wireless devices. Equipped with integrated 4G/LTE radio, the SecureHub seamlessly integrates with the HKC SecureComm platform. For added reliability, the panel includes Wi-Fi and Ethernet for backup communication to SecureComm. The panel's built-in Power Supply Unit and included battery ensure over 12 hours of operation during mains power outages.

- **Impressive Wireless Capacity:**

Supports up to 70 wireless devices such as: Contact/Inertia Sensor, PIR, Smoke, Heat & CO Sensor, Panic Button, Siren & Keyfob

- **Reliable Communication Paths:**

Integrated 4G/LTE (with 2G fallback), Wi-Fi, and Ethernet for faster, more reliable data transfer

- **Flexible Power Options:**

Integrated PSU with onboard lithium polymer battery supporting 12+ hours standby - also allows for system commissioning in the absence of mains power.

- **SecureComm Integration:**

Gives the user remote access via the SecureComm smartphone app and Cloud platform and Engineer access via SmartLink700 for ultimate control

- Certified to EN50131 Grade 2

The **Smart Choice** for
the **Professional Installer**

Exploring Your SecureHub



Key Features

- Discreet, modern design
- Quick and easy installation
- Supports up to 70 HKC wireless devices, keypads, sensors etc.
- Up to 32 users with programmable descriptions & options
- Easy to use menus that follow legacy HKC equipment
- Alarm notifications via Smartphone app and SMS text messaging
- Jam Detection & Heartbeat connection monitored
- Supports IP Reporting to Monitoring Centre/ARC
- Signals Monitoring Centre/ARC in the event of a loss of communication
- Supports high-speed upload/download via SmartLink700 engineer software
- Integrated SecureComm 4G data World SIM card

Technical Specifications

Security Grade	PD 6662:2010, EN 50131-1:2006+A2(Grade 2) EN 50131-6(Grade 2)
Temp / Humidity	-10°C to +40°C / 75% non-condensing (Class II)
Power Supply	Mains Input: 400mA (max.), 230Vac +10%/-15%, 50Hz
Battery	Lithium Polymer 4000mAh. Max. recharge time 7h
Product Weight Size	550g 176mm x 176mm x 43mm

The **Smart Choice** for
the **Professional Installer**